

# BT BMS-Tec<sup>®</sup> – Audio Control & Instrumentation Cables

2 – 3 – 4 – 6 or 8 Cores

18AWG (7x26), Flexible Bare Copper, Overall Screen, HFFR Sheath

BT Cables Part No: C1721 – C1723 – C1725 – C1727 – C1729

## Applications

Screened Multi-Conductor cables suitable for Audio, Control, Instrumentation and Building Management Systems (BMS)

## Sector

BT BMS-TEC™  
Audio, Control & Instrumentation

## Standard References

(BS) EN 50290-2  
IEC 60754-1 & 2  
IEC 61034  
IEC 60332-3C  
RoHS directives

## Design

### 1. Conductor

N x Bare Copper wire,  
18AWG flexible

### 2. Insulation

Polyolefin  
Core 1: Black  
Core 2: Red  
Core 3: White  
Core 4: Green  
Core 5: Brown  
Core 6: Blue  
Core 7: Orange  
Core 8: Yellow

### 3. Drain Wire

24 AWG (7 x 32) Tinned Copper

### 4. Screen

Aluminium/Polyester 100% Coverage

### 5. Ripcord

### 6. Sheath Material

Flame-Retardant  
Halogen Free (HFFR)  
Standard colour: purple

### Standard Put Up Length

305 metres



## Physical Characteristics

BTCL Part Number	Unit	C1721	C1723	C1725	C1727	C1729
No of cores x 18AWG (7 x 26)		2	3	4	6	8
Nom. Diameter Conductor	mm	1.2	1.2	1.2	1.2	1.2
Nom. Radial Thickness Insulation	mm	0.25	0.25	0.25	0.25	0.25
Nom. Radial Thickness Sheath	mm	0.8	0.8	0.8	0.8	0.8
Nom. Overall Diameter	mm	5.1	5.4	5.8	6.8	7.3

## Electrical Characteristics

BTCL Part Number	Unit	C1721	C1723	C1725	C1727	C1729
No of cores x 18AWG (7 x 26)		2	3	4	6	8
Max. DC Resistance Conductor	Ω/km	22.7	22.7	22.7	22.7	22.7
Max. DC Resistance Screen	Ω/km	78.5	78.5	78.5	78.5	78.5
Capacitance conductor to conductor	pF/m	175	150	150	160	160
Nominal Inductance	μH/m	0.5	0.5	0.5	0.5	0.5
Max. Recommended Current at 25°C	Amps	5	5	4	3.5	3.5
Max. Operating Voltage	Vrms	300	300	300	300	300

## Miscellaneous

BTCL Part Number	Unit	C1721	C1723	C1725	C1727	C1729
No of cores x 18AWG (7 x 26)		2	3	4	6	8
Operating Temperature	°C	-25 / +75				
Max. Recommended Pulling Tension	N	200	299	399	600	797
Min. Bend Radius (install)	mm	51	54	58	68	73
Nominal Cable Weight	kg/km	37.9	48.8	59.3	82	102.5